

PROGRAM SIGNAL BLOCKING SYSTEM

The present invention relates to a system for processing and outputting a program signal, such as a television or a radio program signal, and more particularly to a system for processing and outputting a program signal in accordance with auxiliary information included with the program signal.

In addition to the video and/or audio program portions of a particular television or radio program, program signals may include auxiliary information. The program and auxiliary information may comprise analog and/or digital signals. An analog signal, such as an NTSC standard television signal, may include auxiliary data during horizontal line intervals within the vertical blanking interval (VBI). For example, closed caption data is included in line 21, field 1 of the VBI and Extended Data Services (XDS) information is included in line 21, field 2 of the VBI. In digital systems, the video signals are usually transmitted in packets, or groups, of data words. Each packet includes identifying information and represents a particular type of information such as video, audio or auxiliary information. An example of a digital television system that processes a packetized digital television signal is the DSS® (Digital Satellite System) receiver manufactured by Thomson Consumer Electronics, Inc., of Indianapolis, Indiana.

One application of auxiliary information relates to the so-called "V-chip" technology which allows users to automatically block out objectionable material from their television receivers. In systems utilizing this technology, program related information included with the program signals provide advisory information about the respective programs. The program advisory information may take several forms, including, but not limited to program ratings that indicate recommended viewer age and/or content ratings that indicate the presence and/or level of objectionable material, such as sex, violence, language, etc., in the program. For example, a proposed program rating system is described in proposed EIA-744 specification entitled, "Transport of Content Advisory Information using Extended Data Service (XDS)."

The V-chip technology examines the program advisory information associated with each selected program signal against a user selected blocking criteria, such as a selected rating blocking level, and blocks out the program signal if the program advisory information meets the user selected blocking criteria. For example, if the blocking level is

09504709-104000

set at "PG", all programs with a rating of "PG" and higher, such as "R", "NC-17" and "X", would be blocked. Blocking the program signal refers to preventing user access to an objectionable program by, for example, rendering the video black or otherwise indecipherable, muting the audio and disabling the display of program related closed caption. When the program advisory information indicates that objectionable material is no longer being received, the V-chip system unblocks the program channel by displaying the video, unmuting the audio and/or enabling the display of program related closed caption.

- 10 One difficulty associated with the V-chip technology described above is the delay time required for a television receiver to receive and decode program related information. Since program related information is transmitted periodically, in between video, audio and other information, a television receiver may experience a delay before receiving and decoding new program related information when a user selects a new channel. For example, the proposed ANSI/EIA-608A technical specification for the transmission of XDS Program Rating packet states that the Program Rating packet should be repeated at intervals no greater than 3 seconds unless delayed by closed caption data. Closed caption data always takes priority as required by law. So if field 2 captions are present, Program Rating packet transmissions may be delayed longer than 3 seconds. Therefore, when a user selects a new channel, the television receiver may take several seconds to detect and decode the new program related information and take appropriate blocking action. The delay is a noticeable period during which a possibly objectionable program remains unblocked and may be viewed by unintended audiences.

A user may attempt to exploit the above described delay and bypass such a blocking feature by repeatedly tuning to a particular channel to view or listen to portions of an objectionable program before the blocking feature can be activated. For example, the user may continually re-select the same channel or continually switch between two or more channels to view or listen to significant portions of an objectionable program.

- 35 Therefore, what is needed is a system for preventing a user from bypassing the blocking feature in a system which uses program related information included with the program signal. In particular, what is needed is a system for preventing a user from exploiting the delay

00504700-101000

associated with detecting, decoding and examining program related information, in order to bypass the blocking feature.

The present invention overcomes the difficulties noted above by providing a system which prevents a user from exploiting the time delay noted above. The present invention is particularly suitable for use in signal output apparatuses that can tune to one of a plurality of signal channels and provide video and/or audio signal outputs. Such apparatuses include, but are not limited to, television receivers, digital satellite receivers, VCR's, video disk players and audio signal receivers.

10 The present system comprises a signal processor which provides an output signal associated with a program signal of a selected signal channel and controls user access to the program signal in response to a determination of whether program related information included in the program signal meets a user selected blocking criteria. User selected  
15 blocking criteria can take many forms including, but not limited to a particular rating blocking level, in which case the system prevents user access to the output signal if the received program related information equals or exceeds the user selected rating blocking level. Program related information may include, but is not limited to, recommended viewer age  
20 ratings, program content ratings, program title and program summary. Upon activation of an appropriate blocking mode, if a new signal channel is selected and a predetermined sequence of signal selections is detected, the processor automatically controls the output signal associated with the newly selected channel in a predetermined manner to prevent user  
25 access to the program associated with the newly selected channel, and continues such control at least until the processor determines whether the blocking criteria is met with respect to the newly selected channel. Preferably, the signal processor continues such control of the output signal at least until the program related information is determined and  
30 compared with a user selected blocking level.

The output signal is controlled in a predetermined manner to prevent user access to the selected program signal. It is to be understood that such manner of control includes any processes and modification to the program signal that render the program, or portions of the program  
35 visually and/or aurally incomprehensible to the user, including, but not limited to, interrupting the signal path, replacing the normal program signal with a blocking level, scrambling the output signal and/or replacing the output signal with an On Screen Display (OSD) signal representing a displayed message indicating activation of the blocking feature. Such

00584709-10000

control methods advantageously result in, for example, blanking the video portion, muting the audio portion, and disabling the closed captions associated with the program.

The predetermined sequence of channel selections may  
5 comprise a predetermined number of re-selections of the previously selected channel and/or re-selections of two or more channels. The present system may be configured such that the above-noted manner of preventing user access only occurs if the newly selected channel had a previously detected program related information which met the user  
10 selected blocking criteria. By automatically controlling the output signal in the above-noted manner when a predetermined sequence of signal channel selections is detected, the present invention prevents a user from accessing objectionable material during the delay time when the program related information is detected and a determination of whether the  
15 blocking criteria is met is performed.

The present system may also be configured such that the blocking feature is active only if a user selects an appropriate blocking mode.

The present system may also be configured such that the  
20 blocking feature is activated only if at least a particular number of predetermined sequences of signal selections occurs over a particular period of time.

The invention will be described with reference to the accompanying drawings, wherein:

25

Fig. 1 is a block diagram of a television system embodying principles of the present invention;

Fig. 2 is a flowchart showing the steps for changing a channel in a television system which does not provide protection against attempts  
30 to bypass a program related information based blocking system; and

Figs. 3-4 are flowcharts showing the steps for changing a channel in a television system in accordance with the present invention which provides protection against attempts to bypass a program related information based blocking system.

35

An exemplary television receiver system 10 shown in Figure 1 includes input terminal 100 which receives radio frequency (RF) television signals, e.g., from an antenna or cable, and applies the television signals to tuner assembly 105. Tuner assembly 105 selects and

amplifies a particular RF signal associated with the selected television channel in response to control signals from controller 110. As used herein, the terms "controller", "control processor", "microprocessor" (or  $\mu P$ ), and "microcomputer" (or  $\mu C$ ) are equivalent and refer to devices which may or may not be in integrated circuit (IC) form and are capable of performing control functions.

As shown in Fig. 1, controller 110 includes central processing unit (CPU) 112, ROM 114 and RAM 116 interconnected via bus 111 and operating in a manner typical of microcomputers such as the ST9 integrated circuit (IC) manufactured by SGS Thomson, Inc. CPU 112 generates control signals to control the output of system 10 in response to software instructions stored in ROM 114 and EEPROM 127 and in response to user-provided command codes received through keyboard 120 and/or infra-red (IR) receiver 122. Controller 110 receives command codes from IR remote control 125 via IR receiver 122.

Control signals generated by controller 110 are provided to other components of system 10, such as tuner 105, via a control bus represented by the path labeled CTRL\_BUS in Fig. 1. A typical implementation of the control bus shown in Fig. 1 includes, but is not limited to, a two-wire serial bus based on the Inter-Integrated Circuit (IIC or I2C) bus protocol supported by Philips.

IR remote control 125 and/or keyboard 120 permit a user to select a particular blocking criteria for automatically blocking objectionable material. The blocking criteria can take many forms including, but not limited to, blocking a program if an associated program related information, such as program ratings, equals or exceeds a user set information or ratings level. An example of an alternative blocking criteria is activating blocking in response to detecting a user-specified word or words in title or program description information included in the program related information. The user selected blocking criteria, which may be a ratings level as noted above, is stored in controller 110 and examined by CPU 112 to block or unblock a program as described further below. The user selection can be made, for example, by selecting a particular blocking mode and/or blocking level from an On Screen Display menu.

When a user selects a particular television channel by activating either keyboard 120 or remote control 125, controller 110 produces a control signal on bus CTRL\_BUS which causes tuner 105 to tune to the RF signal of the selected channel. Tuner 105 outputs an intermediate

frequency (IF) signal corresponding to the tuned channel to IF processor 130. IF processor 130 includes circuits such as, but not limited to, a video IF (VIF) amplifying stage, an AFT circuit, a video detector, and a sound IF (SIF) amplifying stage for processing the IF signal to produce baseband composite video signal VIDEO and sound carrier signal AUDIO. Audio signal processor 135 includes an audio detector and a stereo decoder that process signal AUDIO to produce a baseband audio signal suitable for driving speaker unit 136. Baseband composite video signal VIDEO from IF processor 130 is applied to video switch 140. Another video signal VIDEO IN may be provided to the present system by an external signal source, for example a VCR, via signal input 102. The external signal source may also provide an audio signal AUDIO IN via signal input 101. Controller 110 controls the respective outputs of video switch 140 and audio processor 135 in response to user selection of the signal source. It is to be understood that a plurality of external signal inputs may be provided to accommodate a plurality of external signal sources, and video signal switch 140 and audio processor 135 may be modified as necessary to allow user selection of a particular external signal source.

Depending on the user selection, video switch 140 provides signal VIDEO1, which is associated with one of the input signals, to video signal processor 155. Video signal processor 155 processes video signal VIDEO1 to produce red, green and blue (R, G and B) output signals RGB which are suitable for coupling to an image display device. Video signal processor 155 performs processing to provide, inter alia, automatic chroma and luma control and enable user-controlled features such as contrast and brightness control.

The RGB signals produced by video signal processor 155 are amplified to appropriately high voltage levels by kinescope driver amplifiers 156 before being coupled to kinescope 158 to display the desired image. The display on kinescope 158 is controlled by vertical and horizontal deflection signals VR and HR, respectively, that are coupled to deflection coils of kinescope 158. Deflection unit 170 produces signals HR and VR in response to horizontal and vertical sync signals HS and VS, respectively, that are separated from the synchronization component of output baseband signal VIDEO. Those parts of the system in Fig. 1 that have been described thus far are known, for example, from the CTC-197 color television chassis manufactured by Thomson Consumer Electronics, Indianapolis, Indiana.

The system shown in Fig. 1 also includes an auxiliary data processor 115 for detecting and decoding various auxiliary information, including program related information, such as program ratings and/or content ratings, included with a video signal. Also, closed caption decoding functions may be included within auxiliary data processor 115 which is coupled with On Screen Display (OSD) processor 117 in order to insert closed caption information into the appropriate portions of the video display. Data processors for extracting auxiliary information from a video signal are conventionally known and typically include a data slicer, timing signal generators, control mechanisms, decoders and memory, among other things. Any one of a number of such conventionally known auxiliary data processors may be used in the present television system. For example, a system suitable for extracting auxiliary information from a video signal is disclosed in U.S. Pat. No. 5,561,469 entitled, "Auxiliary Video Data Slicer with Multi-Mode Peak Detection for Determining Sync and Data Slicing Levels."

Auxiliary data processor 115 detects and decodes program related information, such as program ratings, included in signal VIDEO1, and provides the program related information to CPU 112. CPU 112 examines the detected program related information and determines whether a user selected blocking criteria is met, for example, by comparing the detected program related information with a user selected blocking level and determining whether the detected program related information equals or exceeds the user selected blocking level.

If the user selected blocking criteria is met, CPU 112 renders the program inaccessible by controlling the output signal in a predetermined manner. It is to be understood that such manner of control includes any processes and modification to the program signal that render the program, or portions of the program visually and/or aurally incomprehensible to the user as noted above. For example, controller 110 provides control signals to disable the output of audio processor 135, disable closed caption output and replace the normal program signal with an appropriate OSD signal, such as a uniform blue screen including a message indicating activation of the blocking feature. If the detected program related information does not meet the user selected blocking criteria, CPU 112 allows video signal processor 155 and audio processor 135 to provide output signals associated with the received signals in the conventional manner.

Fig. 2 is a flowchart showing the steps taken by a television system which is not configured to prevent a user from exploiting the delay discussed above. When a user initiates a channel change in step 200, the television system performs a channel blanking in step 202, tunes to a newly selected channel in step 204, and then unblanks the television display in step 206. That is, the newly selected channel is momentarily blanked while the channel is being tuned, but is immediately unblanked after tuner 105 tunes the program signal associated with the new channel.

10 After the new channel has been tuned and unblanked, the television system determines whether the V-chip channel blocking feature is enabled in step 208. If not, the system exits from the program in step 210. If the blocking feature is enabled, the system sets a V-chip Packet Timer to zero and begins incrementing the timer in step 212. The  
15 television system then monitors line 21 XDS data for program related information in step 214.

Once a valid XDS program related information packet has been detected and decoded in step 216, the system resets the V-chip Packet Timer to zero and begins incrementing the timer in a predetermined  
20 manner in step 220. The system then compares the newly detected program related information with a user selected blocking level in step 222 to determine whether the user selected blocking criteria is met. If the blocking criteria is met, i.e., the newly detected program related information equals or exceeds the user selected blocking level, the system  
25 blocks user access to the channel in step 226 by controlling the output signal as described above, and returns to step 214 to repeat the process of detecting and comparing program related information and blocking/unblocking the channel as necessary. If the blocking criteria is not met, i.e., the newly detected program related information is less than  
30 the selected blocking level in step 222, the system allows user access to the program associated with the newly selected channel and returns to step 214 to repeat the monitoring and blocking process as noted above.

Also, if the television system fails to detect a new program related information within a predetermined period of time as determined  
35 by the incrementing of the V-chip Packet Timer, the television system will allow user access to the channel, or maintain the channel unblocked, and return to step 214 to repeat the process as noted above. Therefore, the television system continually attempts to detect new program related



information and determine whether a user selected blocking criteria is met to control user access to the received program signal.

However, it can be seen that user access to the channel occurs in step 206 prior to the detection of new program related information and determination of whether the blocking criteria is met when a user selects a new channel. As discussed above, a significant amount of time may elapse before new program related information is detected and processed, thereby possibly allowing unintended access to objectionable material.

Figs. 3-4 are flowcharts showing the steps performed by a system according to the present invention which provides protection against a user's attempt to exploit the above-noted delay. The features shown in Figs. 3-4 can be enabled and controlled by a user, e.g., by using an On Screen Display menu. Access to enable and control the blocking features may be password protected, i.e., require a user to enter a correct password to prevent unauthorized users from modifying previously established settings. Methods for incorporating these features and the steps described below may be programmed into controller 110 using conventionally known methods.

Again, when a user initiates a channel change in step 230, the present system performs a channel change blanking in step 232 and tunes in the new channel in step 234. However, after tuning in the new channel, and before unblanking the television display, the present system determines whether the program related information based channel blocking feature is enabled by the user in step 236. If not, the system allows user access to the channel in step 264 and exits the program in step 266.

If the channel blocking feature is enabled, the present system determines in step 238 whether the newly selected channel is the same as the previously selected channel in step 238. This determination may provide an indication that the user is continually re-tuning to the same channel in an attempt to bypass the program related information based blocking feature. If the newly selected channel is the same as the previously selected channel, the system may go through 2 additional optional steps or go immediately to step 268 wherein user access to the new channel is prevented and the process of determining a program related information and whether the user selected blocking criteria is met is performed thereafter.

In the first optional step 246, the system determines whether the newly selected channel previously contained objectionable material as

10

indicated by its previously detected program related information. Using previously detected program related information enables the required program related information to be quickly determined. Step 246 may further include a determination of whether the newly selected channel's previously detected program related information was detected within a predetermined period of time. This prevents a decision to blank/unblank a channel from being based on program related information that is no longer relevant. For this purpose, the program related information of the previously selected channel and/or the channel previous to the previously selected channel may be stored in controller 110 for a predetermined period of time.

Alternatively, a counter or a timer may be used to determine how long ago a stored program related information was determined. Conventional methods may be used to store a previously detected program related information and determine how long ago the information was detected. If the newly selected channel's previously detected program related information did not indicate objectionable material within a predetermined period of time, the present system allows user access to the channel through steps 242 and 244. It can be seen that optional step 246 allows the user to quickly switch back to a previously selected channel when the user does not intend to bypass the program related information based blocking system.

If the present system determines in optional step 246 that the newly selected channel's previously detected program related information indicated objectionable material, optional step 261 may be inserted to determine whether the user is repeatedly re-tuning to the same channel. Continually re-tuning to the same channel for at least a predetermined number of times is further indication that the user is trying to bypass the program related information based blocking feature. Requiring a predetermined number of re-tunes may avoid inconvenience to users not attempting to bypass the blocking feature.

Optional step 261 comprises updating a Same Channel Counter in step 260 and comparing the Same Channel Counter with a preselected value, which may be preprogrammed or user selectable. If the Same Channel Counter is less than the preselected/preprogrammed value, the system allows user access to the channel in step 244. However, if the Same Channel Counter is equal to or exceeds the preselected/preprogrammed value, the present system prevents user access to the new channel and proceeds to detect the program related

11

information and determine whether the user selected blocking criteria is met in steps 272-284.

It can be seen that steps 270-284 correspond to steps 212-226 of the system described above in relation to Fig. 2. Essentially, the present system seeks to continuously detect program related information within a predetermined amount of time, then determine whether a user selected blocking criteria is met by comparing the detected program related information with a user selected program related information and controls user access to the selected channel based on the determination.

Further, the present system provides an additional layer of protection against attempts to bypass the program related information blocking feature by continually switching between two different channels. This protection is provided by steps 240-244. Once the system determines in step 238 that the newly selected channel is not the same as the previously selected channel, step 240 determines whether the newly selected channel is the same as the channel selected immediately prior to the previously selected channel. An affirmative response to step 240 indicates that the user may be switching back and forth between two channels to exploit the delay time discussed above. In that case, the system again goes to optional step 246 to determine whether objectionable material was indicated in the channel selected prior to the previously selected channel, and if so, prevents access to that channel. Again optional step 261 may be inserted to allow a predetermined number of channel switches before the program related information based blocking feature is activated. If optional steps 246 and 261 are not present, the system goes to step 268 to keep the new channel blanked.

It can be seen that step 240 may be modified as necessary to prevent the user from bypassing the program related information based blocking system by rotating through a predetermined number of channels.

If the newly selected channel is not the same as either the previously selected channel or the channel previous to the previously selected channel, the present system sets the Same Channel Counter to 0 in step 242, allows user access to the channel in step 244 and goes into the routine for detecting program related information and determining whether a user selected blocking criteria is met as indicated in steps 270-284.

It will be apparent to those skilled in the art that although the invention has been described in terms of an exemplary embodiment,

modifications and changes may be made to the disclosed embodiment without departing from the essence of the invention.

It is herein recognized that the channel blanking described above may be accomplished using any one of a number of conventionally known methods, or combination of methods, for example by using the normal channel change blanking mechanism already built into a signal receiver together with another blanking mechanism to provide additional blanking beyond the normal channel change blanking period, or by using the normal channel change blanking mechanism wherein the blanking period is extended as desired.

Also, the present series of steps shown in Figs. 3-4 may be implemented for a variety of signal formats, both analog and digital, wherein auxiliary information is included with program signals. The above-described system and method may be adapted for use with any signal receiving system which can tune to one of a plurality of signal channels and provide an output signal associated with the tuned signal channel. As such, the present invention may be adapted for use with, but is not limited to, televisions adapted for NTSC, PAL or SECAM signals, digital television receivers, such as digital satellite signal receivers and HDTV receivers, VCRs, and internet based audio/video program systems.

Further, the present apparatus may be modified to compile a record of the number of attempts to re-select a channel that often includes objectionable programs. The compiled record may then be used to automatically block out certain channels or give the user an option of locking out certain channels.

Additionally, the present apparatus may be modified to control the output signal in a predetermined manner based on the number of attempts to re-select a particular channel in a given time period. Again, such an apparatus may be equipped with a recording mechanism to provide a record of the sequence of channel selections and to automatically block out or give the user an option of blocking out certain channels. Using the present apparatus in conjunction with a timer and a record of the sequence of channel selections, the apparatus may automatically block out or give the user an option of blocking out certain channels during certain time period.

Further, the present apparatus may be adapted for use with a television system having multiple signal inputs, wherein the apparatus automatically blocks an output signal associated with an external signal source, upon user selection of the external signal source, at least until

program related information associated with a program signal from the external signal source is detected, and a determination of whether the user selected blocking criteria is met for the program signal from the external signal source is performed.

5           Therefore, it is to be understood that the present invention is intended to cover all modifications as would fall within the true scope and spirit of the present invention.

2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734 2735 2736 2737 2738 2739 2740 2741 2742 2743 2744 2745 2746 2747 2748 2749 2750 2751 2752 2753 2754 2755 2756 2757 2758 2759 2760 2761 2762 2763 2764 2765 2766 2767 2768 2769 2770 2771 2772 2773 2774 2775 2776 2777 2778 2779 2780 2781 2782 2783 2784 2785 2786 2787 2788 2789 2790 2791 2792 2793 2794 2795 2796 2797 2798 2799 2800 2801 2802 2803 2804 2805 2806 2807 2808 2809 2810 2811 2812 2813 2814 2815 2816 2817 2